

# DLT-V6210 Datasheet



## Rugged, sunlight readable Vehicle Mount Terminal

- 10.4" Color-TFT, 600 or 1300 cd/m<sup>2</sup> supporting indoor and outdoor operations
- Break-proven, abrasion-resistant PCT touchscreen
- Large temperature range to handle cold storage and hot, humid environments
- Fully rugged, IP65 and 5M3 for the complete system

The DLT-V6210 is a very rugged vehicle mount terminal designed for efficiency in logistics. With IP65 standard for the complete system, a large operating temperature range and extrem robust mechanical design it supports operations within harsh work environment. Coming with a abrasion resistive and scratch proven projected capacitive multi touchscreen the device withstands physical effects. The DLT-V6210 supports operations under bright light conditions with an optional sunlight readable display. The low profile diversity Wi-Fi antenna, designed for the logistic approach, is perfectly matched to the environmental conditions.


## Specification

System	CPU Mass storage memory	Intel® Atom™ Baytrail E3825 Dual Core 1.33 GHz with 4 GB RAM 32 GB CFAST
Dimensions/Weight		Width x height x depth in mm: 285 x 256 x 70 3.2 kg
Housing		Completely sealed, fanless design, coated aluminium
Display		Color-TFT 10.4" XGA 1024 x 768, 600 or 1300 cd/m <sup>2</sup>
Touchscreen		Projected capacitive touchscreen (PCT), multi-touch
Front keys		3 front keys (1 x Power, 1 x brightness up, 1 x brightness down)
Software	Operating systems	WES7, WE8S, Win 10 IoT Ent., WIN7P, Linux WEC7 (3GB partition visible, expandable up to 29GB)
Communication	Wi-Fi WPAN LAN	Wi-Fi IEEE 802.11 a/b/g/n Bluetooth 4.0 2 x LAN RJ45 10/100/1000 MBit/s
Interfaces	Serial USB RSMA	1 x RS-232; 5 VDC 2 x USB HOST A type, 5 VDC 500 mA 1 x RSMA for external antenna (Wi-Fi), optional
Audio/Voice		Speaker integrated
Power supply (internal)		12/24/48 VDC nominal voltages Automatic switch-on/switch-off function via vehicle ignition
Environmental	IP protection class Operating temperature Relative humidity Shock/Vibration Shock resistance touchscreen	IP65 for the complete system -30 to +50 °C (-22 to +122 °F) 10 to 95% at 25°C, non condensing Class 5M3 according to EN 60721-3-5, US Highway Truck as MIL-STD 810G IK 08
Approvals		EU: CE Immunity Class A, Emission Class B USA: FCC Class B Taiwan: BSMI / NCC Japan: TELEC China: CCC / SRRC


Data sheet V1.04 © by DLog GmbH 04/2017. Information is subject to change. Product names are in most cases also registered trademarks and are thus subject to law.

# DLT-V6210 Datasheet

## Dimensions (in mm)



## Connectors



## Advantech-DLoG Partner Contact

## Accessories

- Scanners with mountings
- Keyboards with mountings
- Stylus with mountings
- Terminal mountings (wide range of mounting brackets, RAM solutions)
- USB Recovery Stick